



Model SLM500 shown with mounting base options (ordered separately)



► Model SLM500

StreamLine® Modular Multifunctional LED Combination Audible/Visual Signal

Model SLM500 is a multifunctional LED beacon and sounder combination developed with a multiple input technology that allows three separate levels of alarm, controllable via wiring selection. This unit offers multiple combinations including independent visual signal, independent audible tone, or a combined audible tone and visual signal.

SLM500 offers three flash patterns (3x strobe, fade and steady) and the option of no visual effect. There are 64 unique tones to select from across two switches (32 tones per switch). The volume of the selected tone is adjustable between 86-105 dBa @ 1m at three output levels (high, medium, low) through an integrated button.

Channel 1 includes a visual signal only. Channel 2 combines an audible tone from switch A to the chosen flash pattern. Channel 3 combines an audible tone from switch B to the chosen flash pattern. Channel 2 and 3 allow the option of audible tone only/no visual effect by cycling through the flash patterns using the integrated button, until the visual effect turns off.

The SLM500 enclosure is made from a self-extinguishing polycarbonate material with high impact and UV resistance.

FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC*
- PLC compatible with PNP or NPN connections (Except Dock Base, only NPN)
- 3 Channels included
 - 1: Visual signal only
 - 2: Visual signal + tone 1
 - 3: Visual signal + tone 2
- The option to have independent audible tone
- 100,000 hour LED
- Five LED lamp/lens colors: Amber, Blue, Clear, Green and Red
- Three flash patterns: 3x strobe (default), fade and steady
- 64 tone options at three adjustable levels
- Seven mounting base options
- Type 3R, IP65 enclosure
- CE Certified
- UL and cUL Listed

*Voltage is dependent on selected base (sold separately)

MODEL	VOLTAGE	FLASH RATE/MINUTE (FLASH MODE)	DECIBELS (MIN.-MAX.)	
			10'	1 M
SLM500 *	12-24VAC/DC or 120-240VAC	85 (+/-10)	76-95	86-105

* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green or (R) Red

MAXIMUM OPERATING CURRENT (mA)					
12VDC	24VDC	12VAC	24VAC	120VAC	240VAC
315	280	375	325	205	115


Weight (unit(s) + base = total weight)

SLM500	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT	2-STACK DOCK BASE	3-STACK DOCK BASE
7.05 oz	12-24VAC/DC	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17 oz 0.26 kg	14.46 oz 0.41 kg	21.16 oz 0.60 kg
0.20 kg	120-240 VAC	—	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35 kg	16.58 oz 0.47 kg	24.69 oz 0.70 kg

StreamLine® Modular Multifunctional LED Combination Audible/Visual Signal (SLM500)

SPECIFICATIONS

Lamp Life: 100,000 Hours
 Light Source: LED
 Operating Temperature: -40°F to 131°F -40°C to 55°C



ACCESSORIES FOR DOCK BASE
















HOW TO ORDER

- Specify model number SLM500 and color
- Specify required mounting base (see chart)
- Optional dome guard
 For shallow mounting base (SLMDG1)
 For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases
 Cable Gland, M20, Gray, 2 Pack (K77700416)
 Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
 1" NPT Adapter (SLMNPT1)
 1/2" NPT Adapter (SLMNPT2)
- Accessories for Dock Base
 Wall Mount Bracket (SLMB23W)
 1/2" NPT Adaptor (SLMB23N)
 Retaining Ring (SLM-RR)
 Light Visor (SLMB23V)

MOUNTING BASE OPTIONS

Mounting bases are rated Type 4X. Final product rating is determined by top module. In combination with SLM500, the unit is Type 3R, IP65. For added protection, install with included retaining ring (SLM-RR).

	Model Number	Base Color	Voltage	
 Shallow Base	SLMBS-012-024GY	Gray	12-24VAC/DC	
	SLMBS-012-024R	Red	12-24VAC/DC	
 Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
	SLMBD-012-024R	Red	12-24VAC/DC	
	SLMBD-120-240GY	Gray	120-240VAC	
	SLMBD-120-240R	Red	120-240VAC	
 Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
	SLMBW-120-240GY	Gray	120-240VAC	
 Pipe Mount	SLMBP-012-024GY*	Gray	12-24VAC/DC	
	SLMBP-120-240GY*	Gray	120-240VAC	
 Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
	SLMBT-120-240GY	Gray	120-240VAC	
 2-Stack Dock Base  3-Stack Dock Base	SLMB2-024GY*	Gray	24VAC/DC	
	SLMB2-120-240GY*	Gray	120-240VAC	
	SLMB3-024GY*	Gray	24VAC/DC	
	SLMB3-120-240GY*	Gray	120-240VAC	

*Installation of included retaining ring is required for pipe and dock bases.